

Chosen Aspects of Polarized Intuitionistic Logic in Theoretical Computer Science

Anna Glenszczyk

Institute of Mathematics
University of Silesia
Katowice

International Student Conference on
Applied Mathematics and Informatics

Malenovice, May 2-5, 2013

Outline

- ▶ Introduction
- ▶ Classical Logic and Intuitionistic Logic
- ▶ Polarized Intuitionistic Logic
- ▶ Conclusions

Logic and Computer Science

- ▶ Curry-Howard Isomorphism
- ▶ functional and logic programming
- ▶ Girard's linear logic

Classical Propositional Logic (**CPC**)

Language:

- atomic formulas
- connectives: $\wedge, \vee, \rightarrow$
- constants: \top (truth) and 0 (falsum)
- ▶ Semantics: truth tables
- ▶ **CPC** is decidable
- ▶ Computational complexity: coNP-complete

Two-valued logic: statements can be either true or false (*tertium non datur*). How much information does the claim $p \vee \neg p$ contain?

Constructivity = Disjunction Property:

If $(A \vee B)$ is a theorem, then A is a theorem or B is a theorem.

Classical Propositional Logic (**CPC**)

Language:

- atomic formulas
- connectives: $\wedge, \vee, \rightarrow$
- constants: \top (truth) and 0 (falsum)
- ▶ Semantics: truth tables
- ▶ **CPC** is decidable
- ▶ Computational complexity: coNP-complete

Two-valued logic: statements can be either true or false (*tertium non datur*). How much information does the claim $p \vee \neg p$ contain?

Constructivity = Disjunction Property:

If $(A \vee B)$ is a theorem, then A is a theorem or B is a theorem.

Classical Propositional Logic (**CPC**)

Language:

- atomic formulas
- connectives: $\wedge, \vee, \rightarrow$
- constants: \top (truth) and 0 (falsum)
- ▶ Semantics: truth tables
- ▶ **CPC** is decidable
- ▶ Computational complexity: coNP-complete

Two-valued logic: statements can be either true or false (*tertium non datur*). How much information does the claim $p \vee \neg p$ contain?

Constructivity = Disjunction Property:

If $(A \vee B)$ is a theorem, then A is a theorem or B is a theorem.

Intuitionistic Propositional Logic (IPC)

Language:

- atomic formulas
- connectives: $\wedge, \vee, \rightarrow$
- constants: \top (truth) and 0 (falsum)
- ▶ no truth values assigned to statements
- ▶ different meaning of connectives: notion of construction
Brouwer-Heyting-Kolmogorow interpretation
- ▶ semantics: algebraic, topological
- ▶ Kripke semantics - rooted finite structures
- ▶ **IPC** is decidable
- ▶ Computational complexity: PSPACE-complete

Intuitionistic Propositional Logic (IPC)

Language:

- atomic formulas
- connectives: $\wedge, \vee, \rightarrow$
- constants: \top (truth) and 0 (falsum)
- ▶ no truth values assigned to statements
- ▶ different meaning of connectives: notion of construction
Brouwer-Heyting-Kolmogorow interpretation
- ▶ semantics: algebraic, topological
- ▶ Kripke semantics - rooted finite structures
- ▶ **IPC** is decidable
- ▶ Computational complexity: PSPACE-complete

Polarized Intuitionistic Logic [Liang and Miller]

Language:

- atomic formulas

- connectives:

Red-Polarized: $\vee, \wedge, \rightarrow$

Green-Polarized: $\wedge^e, \vee^e, \multimap$

- constants: **0**, **1** ("intuitionistic"), \perp , \top ("classical")

- ▶ Two negations: $\sim A = A \rightarrow 0$ and $\neg A = A \rightarrow \perp$

- ▶ all atoms except \perp and \top are **red**

- ▶ **intuitionistic formulas** are built up from atoms and red connectives

- ▶ **classical formulas** are built up from atoms and green connectives

- ▶ duality operator connects green and red operators

Polarized Intuitionistic Logic [Liang and Miller]

Language:

- atomic formulas
 - connectives:
 - Red-Polarized:** $\vee, \wedge, \rightarrow$
 - Green-Polarized:** $\wedge^e, \vee^e, \multimap$
 - constants: **0, 1** ("intuitionistic"), \perp, \top ("classical")
-
- ▶ Two negations: $\sim A = A \rightarrow 0$ and $\neg A = A \rightarrow \perp$
 - ▶ all atoms except \perp and \top are **red**
 - ▶ **intuitionistic formulas** are built up from atoms and red connectives
 - ▶ **classical formulas** are built up from atoms and green connectives
 - ▶ duality operator connects green and red operators

Duality operator $(\cdot)^\perp$

- ▶ $(A \vee^e B)^\perp = A^\perp \wedge B^\perp$
- ▶ $(A \wedge^e B)^\perp = A^\perp \vee B^\perp$
- ▶ $(A \propto B)^\perp = A \rightarrow B^\perp$
- ▶ $\perp^\perp = 1$
- ▶ $\top^\perp = 0$

Duality operator is involutive: $(A^\perp)^\perp = A$

Duality operator $(\cdot)^\perp$

- ▶ $(A \vee^e B)^\perp = A^\perp \wedge B^\perp$
- ▶ $(A \wedge^e B)^\perp = A^\perp \vee B^\perp$
- ▶ $(A \propto B)^\perp = A \rightarrow B^\perp$
- ▶ $\perp^\perp = 1$
- ▶ $\top^\perp = 0$

Duality operator is involutive: $(A^\perp)^\perp = A$

Examples

- ▶ classical formula

$$(p^\perp \vee^e q) \vee^e (q^\perp \vee^e p)$$

- ▶ intuitionistic formula

$$(\neg p \vee \neg q) \rightarrow \neg(p \wedge q)$$

- ▶ PIL formula

$$((p \propto q^\perp) \vee p^\perp) \vee^e q$$

Kripke semantics for PIL

Hybrid Model: $\langle W, \preceq, C, \Vdash \rangle$

- ▶ \preceq is a partial ordering on non-empty set W
- ▶ \Vdash is a monotonic *forcing* relation between elements of W and sets of atomic formulas
- ▶ $C \subseteq W$ is a set of "classical worlds"
- ▶ $\Delta_u = \{k \mid k \in C \text{ and } u \preceq k\}$
- ▶ $\Delta_k = \{k\}$ for all $k \in C$
- ▶ if $\Delta_u = \emptyset$ then u is *imaginary* or \perp -inconsistent

Kripke semantics for PIL

Hybrid Model: $\langle W, \preceq, C, \Vdash \rangle$

- ▶ \preceq is a partial ordering on non-empty set W
- ▶ \Vdash is a monotonic *forcing* relation between elements of W and sets of atomic formulas
- ▶ $C \subseteq W$ is a set of "classical worlds"
- ▶ $\Delta_u = \{k \mid k \in C \text{ and } u \preceq k\}$
- ▶ $\Delta_k = \{k\}$ for all $k \in C$
- ▶ if $\Delta_u = \emptyset$ then u is **imaginary** or \perp -inconsistent

Kripke semantics for PIL

Forcing of formulas for $u, v \in W; c \in C$:

- ▶ $u \Vdash 1$ and $u \nVdash 0$
- ▶ $u \Vdash A \vee B$ iff $u \Vdash A$ or $u \Vdash B$
- ▶ $u \Vdash A \wedge B$ iff $u \Vdash A$ and $u \Vdash B$
- ▶ $u \Vdash A \rightarrow B$ iff for all $v \geq u$ if $v \Vdash A$ then $v \Vdash B$
- ▶ $c \Vdash a^\perp$ iff $c \nVdash a$
- ▶ $c \Vdash \top$ and $c \nVdash \perp$
- ▶ $c \Vdash A \vee^e B$ iff $c \Vdash A$ or $c \Vdash B$
- ▶ $c \Vdash A \wedge^e B$ iff $c \Vdash A$ and $c \Vdash B$
- ▶ $c \Vdash A \propto B$ iff for some $v \geq c$, $v \Vdash A$ and $v \nVdash B^\perp$

Kripke semantics for PIL

Forcing of formulas for $u, v \in W; c \in C$:

- ▶ $u \Vdash 1$ and $u \nVdash 0$
- ▶ $u \Vdash A \vee B$ iff $u \Vdash A$ or $u \Vdash B$
- ▶ $u \Vdash A \wedge B$ iff $u \Vdash A$ and $u \Vdash B$
- ▶ $u \Vdash A \rightarrow B$ iff for all $v \geq u$ if $v \Vdash A$ then $v \Vdash B$
- ▶ $c \Vdash a^\perp$ iff $c \nVdash a$
- ▶ $c \Vdash \top$ and $c \nVdash \perp$
- ▶ $c \Vdash A \vee^e B$ iff $c \Vdash A$ or $c \Vdash B$
- ▶ $c \Vdash A \wedge^e B$ iff $c \Vdash A$ and $c \Vdash B$
- ▶ $c \Vdash A \propto B$ iff for some $v \geq c$, $v \Vdash A$ and $v \nVdash B^\perp$

Properties of PIL

- ▶ simple and expressive semantics
- ▶ proof system in the form of Gentzen calculus
- ▶ simple language
- ▶ decidability

What is the computational complexity of PIL?

Properties of PIL

- ▶ simple and expressive semantics
- ▶ proof system in the form of Gentzen calculus
- ▶ simple language
- ▶ decidability

What is the computational complexity of PIL?

Conjecture

Propositional fragment of PIL is PSPACE-complete

PSPACE-completeness - the Path of Wisdom

- ▶ Ladner's algorithm for modal logic S4
- ▶ Complexity of IPC: Tarski's translation
- ▶ Sequent Calculus for IPC by Dyckhoff
- ▶ Intuitionistic Control Logic

Intuitionistic Control Logic [Liang nad Miller]

Language:

- countably many atomic formulas
 - connectives: $\wedge, \vee, \rightarrow$
 - constants: $\top, 0, \perp$
- $C = \{\mathbf{r}\}$
- All worlds properly above \mathbf{r} force \perp , but not \mathbf{r} itself
- A formula that does not contain \perp as a subformula is valid in ICL if and only if it is valid in intuitionistic logic

Algorithm for ICL

Procedure of creating a world in a model for ICL:

$$ICL-W(\mathcal{T}, \mathcal{F}, \tilde{\mathcal{T}}, \tilde{\mathcal{T}}_{\rightarrow}, \tilde{\mathcal{F}}_{\rightarrow}, \mathcal{L})$$

where

- ▶ \mathcal{T}, \mathcal{F} are sets of formulas respectively forced and not forced in current world
- ▶ $\tilde{\mathcal{T}}$ is a set of formulas already forced in previous worlds
- ▶ $\tilde{\mathcal{T}}_{\rightarrow}$ is a set of pairs of formulas; stores information about forced implication
- ▶ $\tilde{\mathcal{F}}_{\rightarrow}$ is a sequence of pairs of subformulas of not forced implication
- ▶ \mathcal{L} is a sequence of labels; stores information about forcing in previous worlds

Algorithm for ICL

Test for $A \in \text{ICL-SATISFIABLE}$

read A

$v \leftarrow \neg \text{ICL-W}(\{\top\}, \{A, \perp, 0\}, \emptyset, \emptyset, \emptyset, \emptyset);$






end

Future work

- ▶ Details of completeness of the procedure
- ▶ Algorithm for Polarized Intuitionistic Logic
- ▶ Other aspects of PIL

Q & A

Thank you for your attention!

-  Dyckhoff R.: *Contraction-free Sequent Calculi for Intuitionistic Logic*. JSL 57 (3), 795–807, 1992
-  Ladner R.: *The computational complexity of provability in systems of modal propositional logic*. SIAM J. Comp. 6 (3), 467–480, 1977
-  Liang Ch., Miller D.: *An Intuitionistic Control Logic*. To appear
-  Liang Ch., Miller D.: *Kripke Semantics and Proof Systems for Combining Intuitionistic Logic and Classical Logic*. Ann. Pure Appl. Logic. 164 (2), 86–111, 2013
-  Sorensen M.H., Urzyczyn P.: *Lectures on the Curry-Howard Isomorphism*. Studies in Logic and the Foundation of Mathematics, vol. 149, Elsevier, 2006